

TECHNICAL DATA SHEET



ULTRABIND PRIMEX

Ultrabind PrimeX is the ultimate primer for resin-bound driveways, designed to seal and reduce porosity in concrete substrates, creating a strong and durable bond between the substrate and the resin-bound screed. With its advanced formula and one-part system, Ultrabind PrimeX makes it easy to achieve a beautiful and long-lasting driveway.

- Creates a strong bond between substrate and system
- Penetrates concrete substrates to seal pores
- Easy to use one-pack system
- Ensure a durable, long-lasting finish

APPEARANCE AND TYPICAL USES

Ultrabind PrimeX is a clear, single-pack resin primer that seals and protects concrete surfaces prior to resin bound application. Typical installations would be concrete driveways. We do not recommend the use of Ultrabind PrimeX on tarmac surfaces.

PACKAGING

Ultrabind Primex is packaged in 5kg, single-pack units.

SURFACE PREPARATION

Ensure the surface is clean and dry before applying Ultrabind PrimeX. We recommend priming for concrete or other solid driveway sources, but do not recommend the use of Ultrabind PrimeX on tarmac surfaces.

APPLICATION

Stir thoroughly before use. Apply by brush or roller in an even, consistent method working backwards across the surface. Repeat the process when touch dry for further coats.

For added strength, you may cast Ultrabind Binding Sand onto the surface whilst applying. This will increase the surface area and give subsequent resin-bound systems more to bond to.

Please note: We recommend 500g - 1kg of binding sand for every m² of surface.

TECHNICAL DATA

Application Temperature	10°C - 30°C
Touch Dry Time at 20°C	2 hours
Hard Dry Time at 20°C	3 - 4 hours
Coverage Rate	10m ² /kg (standard surface) 5m ² /kg (porous surface)
Recommended Coats	1 (standard surface) 2 (porous substrate)
Storage Temp	5°C - 30°C
Shelf Life	12 months

GENERAL GUIDANCE NOTICE

This Data Sheet is for general purposes and may contain information which is not appropriate for certain conditions of use. All information contained within is accordingly given freely by Resincoat in good faith, without guarantee. Further information on this product and the data contained within this sheet can be obtained from our technical department. You can call us on 0330 0570 695 where we will provide free technical advice for your project.