

TECHNICAL DATA SHEET

ULTRABIND **REVIVE**



Ultrabind Revive is a resin-bound driveway rejuvenator that restores the look of old and tired surfaces, extending their lifespan and saving money that would otherwise so on a complete surface replacement. This solvent-based seal enhances the colour and shine of the surface, whilst the application process is both quick and easy.

- Restores the shine of worn resin-bound surfaces
- Helps extend the lifespan of your driveway
- Quick and easy to apply
- Increases surface resilience
- Cost-effective way to maintain surface

APPEARANCE AND TYPICAL USES

Ultrabind Revive, a glossy resin reviver, rejuvenates worn, faded resin-bound surfaces, such as driveways, pathways and other outdoor surfaces. It's the quick, efficient solution for enhancing both residential and commercial properties.

TECHNICAL DATA

Application Temperature	10°C - 30°C
Touch Dry Time at 20°C	60 - 90 minutes
Hard Dry Time at 20°C	18 - 24 hours
Coverage Rate	3 - 7m ² /kg (standard surface)
Recommended Coats	1 (standard surface) 2 (porous substrate)
Pot Life at 20°C	20 - 30 minutes
Shelf Life	12 months

PACKAGING

Ultrabind Revive is packaged in 4kg, twin-packed units that require mixing together before use.

SURFACE PREPARATION

Before applying Ultrabind Revive, thoroughly clean the resin-bound surface of any debris, dirt, or dust using a broom or blower. For deeper cleans, use a gentle power washer, ensuring to dry thoroughly after use. Inspect and repair any damages or cracks on the surface. Confirm the surface is fully dry before application, as moisture can hinder the effectiveness of Ultrabind Revive.

MIXING

Mix all of Part B into your Part A unit using a drill with a mixing paddle attachment on a slow speed for 90 seconds.

APPLICATION

Applying Ultrabind Revive is straightforward using the roller method. Start by mixing the two-pack resin system as per the instructions. Once thoroughly mixed, pour the mixture onto the clean and dry resin-bound surface. Using a nylon bonded roller for an even application, work in a systematic manner to cover the entire area. The freshly revived surface should not be exposed to rain or frost within the first 24 hours from application.

GENERAL GUIDANCE NOTICE

This Data Sheet is for general purposes and may contain information which is not appropriate for certain conditions of use. All information contained within is accordingly given freely by Resincoat in good faith, without guarantee. Further information on this product and the data contained within this sheet can be obtained from our technical department. You can call us on 0330 0570 695 where we will provide free technical advice for your project.